MECONCEPTS

Step 1:

Jack the vehicle up and support the font end with jack stands.

Step 2:

Using a trim panel removal tool, remove the (8) plastic clips securing the plastic radiator cover to the support and remove it from the vehicle.



Step 3: Remove the (6) 8mm bolts, and (2) 6mm screws securing the bumper cover



Step 4:

Support the front of the car so you can access the bumper splash shield. **Note there are two versions of the splash shield. Both are attached in similar locations



Step 5:On each side of the bumper, remove the plastic clips holding the fender liner to the bumper.



18+ Lower Grille

Contents:

Tools Required:

(1) Lower Grille

Jack & Jack Stands 7mm, 8mm, 10mm Sockets

Ratchet

Trim Panel Removal Tool Flat Head Screw Driver

Step 6:

From the top between the fender, locate and remove the (2) 10mm nuts. **Note: Using a extension and swivel may be necessary.



Step 7:

With the splash shield removed, you can access the plugs for the turn signals and fog lights. Unplug all (3) plugs.



USER INSTRUCTIONS 406358

Step 8:

Once the bumper cover is ready to remove, using firm pressure pull the edge of the bumper down to pop it from the clip. Have a helper support one side so that you don't scratch the paint. Slowly remove the bumper and support it on a soft non-abrasive surface.



Step 9: Begin by removing the plastic bumper brace. Gently bend tabs as needed to remove support.




Step 10:

Next you will remove the factory grille by manipulating the tabs with a trim panel removal tool so that you can pull the grille away from the bumper cover. **Note this can be a little tricky take your time.



Step 11:

Install the MP Concepts grille making sure all clips are properly aligned. Once all clips are aligned use firm pressure to snap the grille into place. Reinstall the front bumper in reverse order.



Step 12:

If your vehicle is equipped with an active shutter system, you may need to trim thr weather stripping around the shutter for proper fitment. You can achive this by using a utility knife.



USER INSTRUCTIONS 406358