

RACER'S CHOICETM

Air Induction System



Installation Instructions for 1994-1995 Ford Mustang 5.0L V8 MAC Part # MA7695



Parts Included:

- 1- MAC 76mm Mass Air Meter with Calibration Tube
- 1- MAC 3410 Silicone Hose with Stainless Steel Hose Clamps
- 1- T20 Torque Head

Note: When installing the MAC MA7695, you will need to remove the 4 bolt adaptor on the air system that you have installed. This adaptor is what the stock Mass Air Meter bolts to.

1. Start by disconnection the wire harness for the MAF sensor.
2. Next loosen the hose clamp on the back side of the stock mass air meter to the aftermarket air tube.
3. Remove the bolts holding the stock mass air meter to the front air tube, and remove the stock mass air meter from the vehicle.
4. Remove the stock MAF sensor from the stock meter using the T20 Torque bit supplied in the kit.
- 4a. At this time it is a good idea to check and be sure that the stock sensor is not dirty in any way. If it is and it needs a cleaning, your local parts store will have have the proper cleaning products. Do not use an air compressor or any liquid cleaners as this will damage the sensor.
5. Remove the front air tube from the vehicle.
6. You will now need to cut the flange off of the air system in order to install the MAC Mass Air Meter. If metal cut the flange off right at the face of the flange. If it is a plastic flange some can be removed with out cutting, as they are glued on. If glued on, be sure that you use a good removal agent and remove all of the glue from the air tube.
7. Install the MAF sensor onto the MAC Meter using the screws provided in the kit.
8. Install the silicone hose with the stainless steel hose clamps to the front air tube and install the air tube into the vehicle.
9. Install the MAC mass air meter between the two hoses and tighten the hose clamps.
10. Check and make sure that all of your hose clamps have been tightened.
11. Reconnect the MAF sensor to the wire harness.
12. You have finished the installation of your MAC MA7695, 76mm Mass Air Meter.

Calibration Tube Chart for the 1994-1995 Mustang 5.0L

GT/Cobra w/Stock Injectors	CT 8
GT w/24lb & Cobra w/30lb	CT 5
GT w/30lb & Cobra w/36/38lb	CT 10
GT w/36/38lb & Cobra w/42lb	CT 9
GT w/42lb	CT 6